



Viking Proline MW Series

ISO 9001:2008 REGISTERED



Model	Inside Overall Length	Outside Overall Length	Install Weight (approx)	Water Level Capacity	6" Boards (optional)	Front Panel Height	Side Height	Tailgate Height	Hoist	Conveyor Width
PL0809MW	8'	9'	1900 lbs	2.9 yd3	4.0 yd3	64"	25"	30"	20 ton	25"
PL1011MW	10'	11'	2200 lbs	3.6 yd3	5.1 yd3	64"	25"	30"	20 ton	25"

Standard Features:

- U-Body construction
- 25:1 Planetary
- Double acting tailgate
- Poly wear plate under chain
- Rear discharge, swing-away spinner
- Threaded rod chain tensioner
- Right rear inspection ladder
- 5083 Aluminum construction
- 3/8" box liner

Options:

- Screens
- Liquid tanks
- Tool box
- Box lighting (Incandescent or LED)
- Air tailgate



November 12, 2010



Viking-Cives (USA)
 14331 Mill Street
 Harrisville, NY 13648
 315-543-2321 Phone
 315-543-2366 Fax

Viking-Cives Ltd.
 P.O. Box 1120 RR#4
 Mount Forest, ON N0G 2L0
 519-323-4433 Phone
 519-323-4608 Fax

Viking-Cives Midwest
 P.O. Box 295 22956 Hwy 61
 Morley, MO 63767
 573-262-3545 Phone
 573-262-3540 Fax