

MW REVERSIBLE PLOWS



STANDARD FEATURES:

- Integral snow shield — exceeds 12" in front of cutting edge
 - 3/16" moldboard skin — fully welded
 - (6) 1/2" x 3 1/2" plate ribs
 - 4" x 4" x 3/4" moldboard base angle
 - Dual compression arm full trip
 - Rubber bumper trip limit
 - (3) attack angle positions 5°- 25°
 - (3) spring tension adjustments

Distributed By:



22956 Highway 61
Morley, MO 63767
P: 573-262-3545
F: 573-262-3540
www.vikingcives.com

MW REVERSIBLE PLOWS

May 2008

PLOW MODEL	LENGTH	HEIGHT	MOLDBOARD	WEIGHT
MW36R10	10'	36"	3/16" Steel	1575 lbs.
MW36R11	11'	36"	3/16" Steel	1620 lbs.
MW41R10	10'	41"	3/16" Steel	1700 lbs.
MW41R11	11'	41"	3/16" Steel	1800 lbs.
MW41R12	12'	41"	3/16" Steel	1875 lbs.
MW48R11	11'	48"	3/16" Steel	1990 lbs.
MW48R12	12'	48"	3/16" Steel	2095 lbs.
MW30R11OW	11'	30" - 50"	3/16" Steel	2000 lbs.
MW30R12OW	12'	30" - 51"	3/16" Steel	2050 lbs.
MW41R10EX	10'	41" - 50"	3/16" Steel	
MW41R11EX	11'	41" - 51"	3/16" Steel	
MW41R12EX	12'	41" - 52"	3/16" Steel	
MW48R14	14'	48"	3/16" Steel	

SOME OPTIONS:

- Screw adjustable assemblies
- Level lift bar & chain
- UQH quick hitch swivel
- Weld on loop
- Pin Swivel
- 29" & 34" Husting Hitch
- Extended curl moldboard
- Carbide cutting edge
- 25 degree moldboard shoes
- Parking jack
- Plow markers
- Rubber deflector
- Dual trip — urethane
- 1/4" poly liner

Distributed By:

